

Certificate of constancy of performance

No. 0672-CPR-0720

In compliance with Regulation (EU) No 305/2011 of the European Parliament and of the Council of 9 March 2011 (the Construction Products Regulation or CPR), this certificate applies to the

Construction Product(s)

Elastomeric bearing

with trade name

SCHREIBER Elastomeric bearing

placed on the market under the name or trade

mark of

Schreiber Brücken-Dehntechnik GmbH

Am Moosbach 10+12 74535 Mainhardt

Germany

produced in the manufacturing plant(s)

Factory S1

This certificate attests that all provisions concerning the assessment and verification of constancy of performance described in

Annex ZA

of the standard(s)

EN 1337-3:2005

under system

1

for the performance set out in this certificate are applied and that the factory production control conducted by the manufacturer is assessed to ensure the

constancy of performance of the construction product.

This certificate was first issued on **2017-07-04**, replaces the EC-Certificate of Conformity (0672-CPD-046.3) to a certification issued on 2010-02-03 and will remain valid as long as neither the harmonised standard, the construction product, the AVCP methods nor the manufacturing conditions in the plant are modified significantly, unless suspended or withdrawn by the notified product certification body.

This document has been translated for informative purpose only. Original version is issued in German. In any case of doubt the German version is valid.



Dipl.-Ing. Siegfried Gerber



Head of Certification Body

Annex 1

to the certificate of constancy of performance No. 0672-CPR-0720

Main performances for the construction product

Elastomeric Bearing

with trade name

SCHREIBER Elastomeric Bearing

steel laminated elastomeric bearing with CR, EG-Certificate of Conformity 1683-CPD-0002 type B, 1683-CPD-0009 type A and 1683-CPD-0010 type C in accordance with EN 1337-3 without or with horizontal sliding part, types 1.2 to 1.8 in accordance with EN 1337-1, for effective bearing temperatures from -40 °C to +50 °C without and -35 to +48 °C with sliding part, for use in building and civil engineering works where requirements on individual bearings are critical.

This Annex is only valid together with the certificate of constancy of performance according EU-BauPVO 0672 – CPR – 0720.

