

Certificate of constancy of performance

No. 0672-CPR-0432

In compliance with Regulation (EU) No 305/2011 of the European Parliament and of the Council of 9 March 2011 (the Construction Products Regulation or CPR), this certificate applies to the

Construction Product(s)

Spherical and cylindrical PTFE bearings

with trade name

SCHREIBER Spherical Bearings, SCHREIBER Cylindrical Bearings

placed on the market under the name or trade mark of Schreiber Brücken-Dehntechnik GmbH

Am Moosbach 10+12 74535 Mainhardt

Germany

produced in the manufacturing plant(s)

Factory S1

This certificate attests that all provisions concerning the assessment and verification of constancy of performance described in

Annex ZA

of the standard(s)

EN 1337-7:2004

under system

1

for the performance set out in this certificate are applied and that the factory production control conducted by the manufacturer is assessed to ensure the

constancy of performance of the construction product.

This certificate was first issued on **2017-07-04**, replaces the EC-Certificate of Conformity (0672-CPD-046.1) to a certification issued on 2005-12-01 and will remain valid as long as neither the harmonised standard, the construction product, the AVCP methods nor the manufacturing conditions in the plant are modified significantly, unless suspended or withdrawn by the notified product certification body.

This document has been translated for informative purpose only. Original version is issued in German. In any case of doubt the German version is valid.



Dipl.-Ing. Siegfried Gerber Head of Certification Body



Annex 1

to the certificate of constancy of performance No. 0672-CPR-0432

Main performances for the construction product

Spherical and cylindrical PTFE bearings

with trade name

SCHREIBER Spherical Bearings, SCHREIBER Cylindrical Bearings

with hard chromium plated spherical cap, horizontal sliding part and external guides in case of unidirectional movable bearings, types 3.1, 3.3, 3.5, 7.1, 7.2, 7.3, 7.4 in accordance with EN 1337-1, for effective bearing temperatures of -35°C to +48°C, for use in building and civil engineering works where requirements on individual bearings are critical,

This Annex is only valid together with the certificate of constancy of performance according EU-BauPVO 0672 – CPR – 0432.

